

## 378 Temperature Controller

Monitor and control temperature in process water



- Analog voltage output
- Proportional bandwidth control
- Set points on front panel
- Large bright red LED screen
- Manual adjustable reset

### Description

Global Water's Temperature Controllers are high performance industrial grade digital indicating, single set point proportional/On-Off controllers for use with type K, J, T and E thermocouples. Thermocouple gain and cold junction are automatically compensated by the Temperature Controller's internal electrode circuits. An accurate 1 mV per display count analog output is provided to interface the Temperature Controller with a recorder, printer and so on. The Temperature Controller uses a bright red LED screen.

The Temperature Controllers are a single set point proportional/On-Off controller. The proportional bandwidth is adjustable from On-Off to 100 °C or 100 °F with built-in hysteresis. The cycle time is factory set to 20 second ± 3 seconds. The Temperature Controllers have a front panel manual adjust reset potentiometer.

The Temperature Controllers are 1/8 DIN front panel mount inside of a plastic housing. Temperature probe connections are made via spade lug connectors.

### Specifications

Model	Type	Range	Resolution	Accuracy
378KC	K	0 to 1000 °C	1 °C	± 0.50% ± 1 count
378KF	K	0 to 1999 °F	1 °F	± 0.50% ± 1 count
378JC	J	0 to 550 °C	1 °C	± 0.40% ± 1 count
378JF	J	0 to 1000 °F	1 °F	± 0.40% ± 1 count

*Hysteresis:* °C model 6 °C (± 3 °C)  
°F model 10 °F (± 5 °F)

*Proportional Band:* Adjustable from on/off to 100 °C or 100 °F with built in hysteresis

*Cycle Time:* 20 ± 3 seconds

*Reset:* Manual adjust

*Operating Temperature:* 0 to 40 °C

*Analog Output:* 1 mV/count, ± 0.30% of span ± 1 mV

*T/C Burnout:* Upscale

*Output Relay:* 8 A at 115 VAC, 4A at 230 VAC, resistive load

*Power Source:* 115/230VAC, ± 10% 50/60 Hz

*Dimensions:* 3.75x2x4.25in (96x48x105mm)

*Weight:* 1 lb (0.38 kgs)

### Options and Accessories

#### 378JC/JF

Temperature Controller

Does not include temperature probe.

#### 378KC/KF

Temperature Controller

Does not include temperature probe.

Contact  
Global Water  
for all your  
instrumentation  
needs:

Water Level

Water Flow

Water Samplers

Water Quality

Weather

Remote Monitoring

Control



**Global Water**  
The Leader in Water Instrumentation

In the U.S. call toll free  
at 1-800-876-1172  
International: 916-638-3429  
Fax: 916-638-3270  
Email: globalw@globalw.com

Visit our online catalog at:  
www.globalw.com  
Our Address:  
11390 Amalgam Way  
Gold River, CA 95670