




Smith-Blair Flanged Coupling Adapters And Dismantling Joints



911



912



913



914



920



921



923



926




932



933



EZWF




971



972



973



975

Smith-Blair FCAs and Dismantling Joints

Model	Product	Application	Pipe Types	Norm. Pipe Sizes	Working Pressure
911	Flange-Lock Flanged Coupling Adapter	Connecting & restraining plain-end pipe to flanged fittings	Ductile Iron, Steel	3" - 48" Ductile Iron 3"- 12" IPS Steel	3"-12" Flange : 175 PSI Greater than 14": 150 PSI
912	Cast Flanged Coupling Adapter	Joining plain-end pipe to flanged valves and fittings	All Types	3"-12"	250 PSI
913	Steel Flanged Coupling Adapter	Joining plain-end pipe to flanged valves and fittings	All Types	3" and larger	3"-12" Flange : 175 PSI Greater than 14": 150 PSI
914	Steel Reducing Flanged Coupling Adapter	Joining plain-end pipe of different outside diameters to flanged valves and fittings	All Types	3" and larger	3"-12" Flange : 175 PSI Greater than 14": 150 PSI
920	Flange-Lock Flanged Coupling Adapter	Connecting & restraining plain-end pipe to flanged fittings	PVC	3"-36"	3"-12" Flange : 175 PSI Greater than 14": 150 PSI
921	Top Bolt Wide Range Flanged Coupling Adapter	Joining a wide range of pipe diameters with unique gasket system to flanged valves and fittings	Ductile Iron, Steel, PVC, Other	2"-12" 16"	175 PSI 150 PSI
923	Flange-Lock Flanged Coupling Adapter	Weldment only Straight and Reducing	PVC, Ductile Iron, Steel	3"-48"	3"-12" Flange : 175 PSI Greater than 14": 150 PSI
926	Meter Coupling	Joining plain-end pipe to oval flanged water meters and joining plain-end pipe to flanged valves and fittings	PVC, Copper, Steel, Cast Iron	1-1/2"-2"	175 PSI
932	Insulating Cast Flanged Coupling Adapter	Joining and insulating plain-end to flanged valves and fittings	Steel, Cast Iron, Ductile Iron	3"-12"	150 PSI
933	Insulating Steel Flanged Coupling Adapter	Joining and insulating plain-end to flanged valves and fittings	Steel, Cast Iron, Ductile Iron, Large Pipe	2" and larger	150 PSI
971	Dismantling Joint (Non-Restraint Joint)	Valve, meter, pump and other flanged fitting installations	Any Class D Flanged Pipe	3" and larger	3"-12" Flange : 175 PSI Greater than 14": 150 PSI
972	Dismantling Joint (Heavy Duty Restraint Joint)	Valve, meter, pump and other flanged fitting installations	Any Class D Flanged Pipe	3" and larger	3"-12" Flange : 175 PSI Greater than 14": 150 PSI
973	Dismantling Joint (Restraint Joint)	Valve, meter, pump and other flanged fitting installations	Any Class D Flanged Pipe	3"-12"	150 PSI
975	Dismantling Joint (Restraint Joint)	Valve, meter, pump and other flanged fitting installations	Any Class D Flanged Pipe	3" and larger	3"-12" Flange : 175 PSI Greater than 14": 150 PSI
EZWF	Maxi-Grip EZ-W Restrained Flanged Coupling Adapter	Connecting and restraining plain-end pipe to flanged pipe	Ductile Iron, PVC, Steel	2"-12"	175 PSI

DISCLAIMER: Information contained in this sales sheet is for sales and marketing purposes only and was accurate at the time of publication. Always refer to smith-blair.com for the most up to date and accurate technical specifications and performance information about Smith-Blair products.

